

# E65 Useries

130mm~372mm



## General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°

## Major Characteristic Parameters

Model Part NO.	Size(mm)			Rated Voltage V	Rated Frequency Hz	Rated Current A	Input Power W	Rated Speed RPM	Maximum Air Flow		Maximum Static Pressure		Sound Level dBA	Weight g
	A	B	C						m <sup>3</sup> /min	CFM	mm-Aq	In-H <sub>2</sub> O		
CE65120A11	120	130	90	110	60	0.31	21	1600	2.0	70.67	6.0	0.236	40	1420
CE65120A22	120	130	90	220	50	0.14	19	1600	2.0	70.67	6.0	0.236	40	1420
CE65190A11	190	200	160	110	60	0.30	22	1100	2.2	77.73	2.6	0.102	43	1530
CE65180A22	190	200	160	220	50	0.16	20	1100	2.2	77.73	2.6	0.102	43	1530
CE65240A11	242	252	192	110	60	0.65	32	1500	3.9	137.80	3.8	0.149	45	1690
CE65240A22	242	252	192	110	50	0.33	30	1500	3.9	137.80	3.8	0.149	45	1690
CE65300A11	303	312	272	110	60	0.68	41	1300	4.5	159.01	4.2	0.165	45	1760
CE65300A22	303	312	272	220	50	0.35	40	1300	4.5	159.01	4.2	0.165	45	1760
CE65360A11	362	372	332	110	60	0.91	51	1300	5.3	187.27	5.0	0.196	47	1820
CE65360A22	362	372	332	220	50	0.45	52	1300	5.3	187.27	5.0	0.196	47	1820
CE65420A11	422	432	382	110	60	0.99	59	1300	5.2	183.74	6.3	0.248	50	1850
CE65420A22	422	432	382	220	50	0.55	58	1300	5.2	183.74	6.3	0.248	50	1850

