

D43 P series

108mm~370mm

General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B				C	V	A	RPM		
CD43090A12	98	108	134	12	0.22	2800	0.8	24	1.8	0.070	36	210
CD43090A24	98	108	134	24	0.18	2800	0.8	24	1.8	0.070	36	210
CD43150A12	160	170	195	12	0.15	2500	1.2	42	1.2	0.047	37	260
CD43150A24	160	170	195	24	0.25	2500	1.2	42	1.2	0.047	37	260
CD43190A12	198	208	239	12	0.33	2400	1.5	53	1.0	0.039	39	300
CD43190A24	198	208	239	24	0.22	2400	1.5	53	1.0	0.039	39	300
CD43240A12	250	260	306	12	0.42	2700	2.2	78	1.1	0.043	43	490
CD43240A24	250	260	306	24	0.30	2700	2.2	78	1.1	0.043	43	490
CD43290A12	300	310	316	12	0.50	2600	2.5	85	1.0	0.039	43	530
CD43290A24	300	310	316	24	0.30	2600	2.5	85	1.0	0.039	43	530
CD43350A12	360	370	416	12	0.55	2500	2.8	95	1.0	0.039	45	570
CD43350A24	360	370	416	24	0.35	2500	2.8	95	1.0	0.039	45	570

